

FLEX-CABLE/NCSI

AIR-COOLED CABLE ORDER FORM

MCM SIZE	TYPE	STYLE	HOLE DIAMETERS	LENGTH IN INCHES	OPTIONS
<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>	<input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/> <input style="width: 30px; height: 20px; border: 1px solid black;" type="text"/>
- S					

MCM SIZE

- 40 = 400MCM
- 50 = 500MCM
- 60 = 600MCM
- 75 = 750MCM
- 10 = 1000MCM
- 12 = 1200MCM
- 15 = 1500MCM
- 20 = 2000MCM

CABLE TYPE

- A = COLOR-FLEX
- X = FLEXTRA
- I = IW-FLEX

STYLE

See Terminal Configuration Chart

HOLE DIAMETERS

- 1717 = 17/32" and 17/32"
- 1721 = 17/32" and 21/32"
- 2121 = 21/32" and 21/32"
- x x x x = CUSTOMER SPECIFIED HOLE DIAMETERS

LENGTH IN INCHES

PLEASE SPECIFY

OPTIONS


- WK = 1 3/8" terminal width for 400-750 MCM sizes.
- P = PERFORATED COVER
- E = EXTENDED COLLAR

EXAMPLE: 12AA1721-18-S
DESCRIPTION: 18 in. 1200MCM COLOR-FLEX WITH 17/32" & 21/32" HOLES IN SILVER PLATED TERMINALS.

For Technical Support or Questions on our products, Please call a FLEX-CABLE representative at 1-800-245-3539 or email us at sales@flexcable.com

AIR-COOLED TERMINAL CONFIGURATION CHART

Standard terminal width is 1-1/4 in. 1-3/8 in. and 1-1/2 in. are available upon request.
See ordering chart for bolt hole diameters.



"B" Thickness	STANDARD		
	MCM	Width	
400		1-1/4	1-3/8
500		0.38	0.35
600		0.44	0.41
750		0.50	0.46
1000		0.63	0.58
1200		0.81	0.74
1500		0.97	0.88
2000		1.22	1.11
		---	---
			1-1/2
			0.67
			0.81
			1.02

